

CL2**Architectural & Engineering Specifications****CL2 (120V, 60 Hz models)**

The amplifier shall be a solid-state two-channel model. Each amplifier channel shall have the ability to operate individually, or paired with the other channel in a bridged configuration to provide increased output voltage over that of an individual channel output.

Front panel controls shall include a rocker switch for selecting power on and off. Rear panel controls shall include a recessed detented rotary control for each channel to adjust input level, a recessed switch to select Stereo or Bridge modes of operation, and a reset switch for the AC mains circuit breaker.

Internal controls shall include a jumper block to allow selection of input sensitivity of either 0.775V or 26 dB gain as a service option. Sensitivity shall be factory-set to 1.4V.

Front panel indicators shall include a green LED to indicate that the amplifier is turned on and power is applied; a red LED for each channel which shall blink to indicate any of the following 5 conditions: 1) When the amplifier is first powered up, until the unit is ready for operation. 2) If the heatsinks reach a temperature above normal working limits. 3) If the transformer thermal protection circuit is activated. 4) If the amplifier wires develop a short circuit, and 5) should the amplifier output stage become non-operational; a red LED for each channel which shall turn on to indicate when distortion of any type becomes audible in the amplifier output; and a green LED for each channel which shall flash dimly to indicate when a low-level signal (> -40 dBm) is present at the input of the amplifier.

Rear-panel connectors shall include a combination XLR and ¼-in (6.35 cm) phone connector in parallel with a three-terminal barrier block for each channel for balanced input connection (on the standard input module); a four-terminal touch-proof barrier block for output connection (on the standard output module); and an RJ11 jack for connection to an external circuit for the purpose of remotely monitoring fault conditions.

The amplifier power requirements shall be 120 VAC, 9.5 A at 60 Hz. A detachable IEC 15A to NEMA 5-15P AC line cord shall be provided for AC connection. Typical quiescent power draw shall be 60 watts.

The amplifier chassis shall be constructed of steel with a durable black

finish. The amplifier shall employ a cooling system consisting of internal heat exchangers, along with a variable-speed cooling fan which shall operate according to internal thermal demand. Airflow through the chassis shall be from front to rear.

The dimensions of the amplifier shall allow for 19 inch (48.3 cm) EIA Standard (RS-310-B) rack mounting. The amplifier shall be 5.25 inches (13.34 cm) tall and 12.25 inches (31.11 cm) deep behind the rack-mounting surface. The amplifier shall weigh 40.3 pounds (18.28 kg).

The amplifier shall be protected against shorted, open or mismatched loads; overloaded power supplies; excessive temperature; chain destruction phenomena; input overload damage; and high-frequency blowups. The amplifier shall protect loudspeakers from input/output DC, large or dangerous DC offsets and turn-on/turn-off transients.

Input Impedance of the amplifier shall be nominally 20 k ohms, balanced; nominally 10 k ohms, unbalanced.

The power amplifier shall meet or exceed the following performance criteria (amplifier in stereo mode with 8 ohm loads and an input sensitivity of 26 dB gain, 1 kHz at rated power unless otherwise specified): Load impedance (safe with all types of loads): 2, 4 & 8 ohm Stereo; 4, 8 & 16 ohm Bridge. Voltage gain, 1 kHz, 1.4V sensitivity: 32.1dB at 4/8 ohm. Output Power at 1 kHz at rated THD; in Stereo mode at 8 ohms: 400 watts per channel; in Stereo mode at 4 ohms: 660 watts per channel; in Stereo mode at 2 ohms: 975 watts per channel; in Bridge mode at 8 ohms: 1,320 watts; in Bridge mode at 4 ohms: 1,950 watts. Frequency Response, 20 Hz to 20 kHz at 1 watt: ± 0.1 dB. Phase Response: ± 15 degrees deviation from linear phase from 20 Hz to 20 kHz at 1 watt. Signal to Noise Ratio, A-Weighted: Better than 105 dB below rated 1-kHz power. Total Harmonic Distortion (THD), 1 kHz at rated power: 0.5% or less true THD from 20 Hz to 20 kHz. Intermodulation Distortion (60 Hz and 7 kHz at 4:1): Less than 0.1% at rated power to 30 dB below rated power at 8 ohms. Damping Factor (8 ohm): Better than 400 from 10 Hz to 400 Hz. Crosstalk, 20 Hz to 20 kHz: Better than 50 dB below rated power. Common Mode Rejection (CMR): Better than 40 dB from 20 Hz to 1 kHz. DC Output Offset (Shorted Input): ± 10 mV.

The amplifier shall be designated the Crown CL2



H A Harman International Company

Crown Audio, Inc.
P.O. Box 1000
Elkhart, IN 46515-1000
TEL: 574-294-8200
FAX: 574-294-8FAX
www.crownaudio.com

Specifications subject to change without prior notice. Latest information available at www.crownaudio.com.
Crown® is a registered trademark of Crown International, Inc.
Printed in U.S.A.
© 2003 Crown Audio, Inc.